

ISBN 978-0-626-33751-3

SANS 60079-28:2016

Edition 2

IEC 60079-28:2015

Edition 2

SOUTH AFRICAN NATIONAL STANDARD

Explosive atmospheres

Part 28: Protection of equipment and transmission systems using optical radiation

This national standard is the identical implementation of IEC 60079-28:2015, and is adopted with the permission of the International Electrotechnical Commission.

WARNING
This document references other
documents normatively.

Published by SABS Standards Division
1 Dr Lategan Road Groenkloof ☒ Private Bag X191 Pretoria 0001
Tel: +27 12 428 7911 Fax: +27 12 344 1568
www.sabs.co.za
© SABS

SABS

SANS 60079-28:2016

Edition 2

IEC 60079-28:2015

Edition 2

Table of changes

| Change No. | Date | Scope |
|-------------------|-------------|--------------|
| | | |

National foreword

This South African standard was approved by National Committee SABS/TC 065, *Explosion prevention*, in accordance with procedures of the SABS Standards Division, in compliance with annex 3 of the WTO/TBT agreement.

This document was approved for publication in October 2016.

This document supersedes SANS 60079-28:2009 (edition 1 as modified by IEC interpretation sheet 1:2014).

Compliance with this document cannot confer immunity from legal obligations.



IEC 60079-28

Edition 2.0 2015-05

INTERNATIONAL STANDARD

NORME INTERNATIONALE



**Explosive atmospheres –
Part 28: Protection of equipment and transmission systems using optical
radiation**

**Atmosphères explosives –
Partie 28: Protection du matériel et des systèmes de transmission utilisant le
rayonnement optique**

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

COMMISSION
ELECTROTECHNIQUE
INTERNATIONALE

ICS 29.260.20

ISBN 978-2-8322-2679-7

**Warning! Make sure that you obtained this publication from an authorized distributor.
Attention! Veuillez vous assurer que vous avez obtenu cette publication via un distributeur agréé.**

CONTENTS

| | |
|--|----|
| FOREWORD..... | 4 |
| INTRODUCTION..... | 8 |
| 1 Scope..... | 9 |
| 2 Normative references | 10 |
| 3 Terms and definitions | 10 |
| 4 General requirements | 13 |
| 5 Types of protection | 13 |
| 5.1 General..... | 13 |
| 5.2 Requirements for inherently safe optical radiation “op is” | 14 |
| 5.2.1 General | 14 |
| 5.2.2 Continuous wave radiation..... | 14 |
| 5.2.3 Pulsed radiation..... | 18 |
| 5.2.4 Ignition tests..... | 19 |
| 5.2.5 Over-power/energy fault protection | 19 |
| 5.3 Requirements for protected optical radiation “op pr” | 20 |
| 5.3.1 General | 20 |
| 5.3.2 Radiation inside optical fibre or cable | 20 |
| 5.3.3 Radiation inside enclosures | 21 |
| 5.4 Optical system with interlock “op sh” | 21 |
| 6 Type verifications and tests | 22 |
| 6.1 Test set-up for ignition tests..... | 22 |
| 6.1.1 General | 22 |
| 6.1.2 Test vessel..... | 22 |
| 6.1.3 Criteria to determine ignition..... | 23 |
| 6.2 Verification of suitability of test set-up for type tests | 23 |
| 6.2.1 Reference gas | 23 |
| 6.2.2 Reference absorber | 23 |
| 6.2.3 Reference test for continuous wave radiation and pulses above 1 s duration | 23 |
| 6.2.4 Reference test for pulsed radiation below 1 ms pulse duration..... | 23 |
| 6.3 Type tests | 24 |
| 6.3.1 Ignition tests with continuous wave radiation and pulses above 1 s duration | 24 |
| 6.3.2 Ignition tests with single pulses less than 1 ms duration | 24 |
| 6.3.3 Tests for pulse trains and pulses from 1 ms to 1 s duration..... | 24 |
| 6.3.4 Absorber targets for type tests..... | 24 |
| 6.3.5 Test acceptance criteria and safety factors | 25 |
| 7 Marking | 25 |
| Annex A (informative) Reference test data | 27 |
| Annex B (informative) Ignition mechanisms..... | 28 |
| Annex C (normative) Ignition hazard assessment..... | 33 |
| Annex D (informative) Typical optical fibre cable design | 35 |
| Annex E (normative) Flow diagram for the assessment of pulses | 36 |
| Bibliography..... | 37 |

| | |
|---|----|
| Figure 1 – Optical ignition delay times and safe boundary curve with safety factor of 2 | 22 |
| Figure B.1 – Minimum radiant igniting power with inert absorber target ($\alpha_{1064 \text{ nm}}=83 \%$, $\alpha_{805 \text{ nm}}=93 \%$) and continuous wave-radiation of 1064 nm | 31 |
| Figure B.2 – Minimum radiant igniting power with inert absorber target ($\alpha_{1064 \text{ nm}}=83 \%$, $\alpha_{805 \text{ nm}}=93 \%$) and continuous wave-radiation (PTB: 1064 nm, HSL: 805 nm, [8]: 803 nm) for some n-alkanes | 32 |
| Figure C.1 – Ignition hazard assessment | 33 |
| Figure D.1 – Example Multi-Fibre Optical Cable Design For Heavy Duty Applications | 35 |
| Figure D.2 – Typical Single Optical Fibre Cable Design | 35 |
| Figure E.1 – Flow diagram for the assessment of pulses according to 5.2.3 | 36 |
| | |
| Table 1 – EPLs achieved by application of types of protection for optical systems | 13 |
| Table 2 – Safe optical power and irradiance for Group I and II equipment, categorized by Equipment Group and temperature class | 15 |
| Table 3 – Safe optical power and irradiance for Group III equipment | 15 |
| Table 4 – Safe limit values for intermediate area, Group I or II, constant power, T1 – T4 atmospheres, equipment Groups IIA, IIB or IIC (Data derived from Figure B.1 including a safety factor) | 16 |
| Table A.1 – Reference values for ignition tests with a mixture of propane in air at 40 °C mixture temperature | 27 |
| Table B.1 – AIT (auto ignition temperature), MESG (maximum experimental safe gap) and measured ignition powers of the chosen combustibles for inert absorbers as the target material ($\alpha_{1064 \text{ nm}}=83 \%$, $\alpha_{805 \text{ nm}}=93 \%$) | 30 |
| Table B.2 – Comparison of measured minimum igniting optical pulse energy ($Q_{e,p}^{i,min}$) at 90 μm beam diameter with auto ignition temperatures (AIT) and minimum ignition energies (MIE) from literature [9] at concentrations in percent by volume (φ) | 32 |